


Artikelnummer/Itemnumber: 476BG

Absperrpfosten, Stahlrohr \varnothing 76 x 2,6 mm, gelb/schwarz, ortsfest, mit Erdanker, ohne Öse

Barrier post, steel tube \varnothing 76 x 2,6 mm, yellow/black, stationary, with ground anchor, without eyelet



Artikelbeschreibung:

Absperrpfosten, Stahlrohr \varnothing 76 x 2,6 mm, mit aufgeschweißter Stahlkappe, ca. 900 mm Überflur, feuerverzinkt und gelb beschichtet mit drei schwarzen Streifen, ortsfest, zum Einbetonieren, mit Erdanker, ohne Öse

Verwendungszweck:

Zum Sichern von Werksgeländen, Maschinen und Anlagen oder Einfahrten.

Technische Daten:

Gewicht: 6,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Barrier post, Steel tube \varnothing 76 x 2,6 mm, with welded steel cap, approx. 900 mm above ground, hot-dip galvanized and coated yellow with three black stripes, stationary, for casting in concrete, with ground anchor, without eyelet

designated purpose:

For protecting work sites, machines and facilities or gateways.

technical specifications:

weight: 6,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated