


Datenblatt/ datasheet

Artikelnummer/Itemnumber: 476PB

Absperrpfosten, Stahlrohr \varnothing 76 x 2,6 mm, ortsfest, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, ohne Öse



Barrier posts, steel tube \varnothing 76 x 2,6 mm, stationary, hot-dip galvanized and white coated with three red reflecting stripes, without eyelet



Artikelbeschreibung:

Absperrpfosten, Stahlrohr \varnothing 76 x 2,6 mm, mit aufgeschweißter Stahlkappe, 900 mm Überflur, ortsfest, für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, feuerverzinkt und weiß beschichtet mit drei rot reflektierenden Leuchtstreifen, ohne Öse

Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

Technische Daten:

Gewicht: 6,00 kg/St
Material:
S235 JR

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

item description:

Barrier post, steel tube \varnothing 76 x 2.6 mm, with welded steel cap, 900 mm above ground, stationary, to be fixed by plugs, with base plate 100 x 150 mm, hot-dip galvanized and white coated with three red reflecting stripes, without eyelet

designated purpose:

For stopping, and securing or saving of areas.

technical specifications:

weight: 6,00 kg/pc
material:
S235 JR

surface:
hot dipped galvanized and powder coated